

account  
 a correct way. \* < ^ ^ " Jp used,  
 ph- b\* . to shops where a peat ^ tol » t  
 otto than the , , , .  
 placed in jig\* ^ f f ^ ° ^ n previously  
 machir, « l at the  
 Let one, and woA \* " £ ? £ \* entirety spoiW.  
 Th« e-  
 e ^ diture of a great < " \* be ^ . ^ , ,  
 too l . 1 > r o of »  
 , , , « , whenever posable, ^ ^ ta shlll, c and a \* = ,  
 as,  
 When the work to be nucm is ^ . . ^ y to  
 have  
 for instance, in the e ^ ™ g ^ ts ^ , , , , ,  
 , »

^ ^ f « i -

1 5 £ ^ ^ "  
 risrs ^ K ? tols \_ luliusl "  
 ^

points will be described m ^ detai ^ ^ ^ armngements  
**Clamping Devices.** - Iht su H b ifidng  
 effectiveness,

should be as simple as P ^ ' ^ ^ Huch as to not  
 r ^ tr ^ ; - " - " \* hii > " iw  
 h1

pressure of the cut aw r u . , lt ion of damps to a  
 jig -

The main pnnaples m th ^ ^ | hr , n H . rato

only hold  
 and the strength of he ^ ^ ^ the strain of the  
 cutting A » « l « . f i n n l v m place, but alw > to w \* . \_  
 . . . , , \_ i h c n «

m order to = t | , ta , , Ham , .  
 part of the faturc rtelt. Oodt  
 U

$\hat{\cdot} \hat{\cdot}$   
however

\*£ ,,,. ,rtl,ri. h ,,», „